


150W Configuration Nomenclature for

LV150U



XY

E.G. LV150U 05 12 12R 48
(Represented 5V/22A, 12V/8A, 12V/2A, 48V/1A)

Meaning	Code	
Output # 1	03	+3.3 Vdc, 30 A/ 15 A
	05	+5 to +5.1 Vdc, 22 A/ 15 A
	24	+24 Vdc, 5.0 A/ 3.8 A
	48	+48 Vdc, 2.5 A/ 1.9 A
	48S	+48 Vdc, 3.125 A/ 1.9 A
	48A	+48 Vdc, 3.55 A/ 1.9 A
	48B	+48 Vdc, 3.55 A/ 1.9 A
Output # 2	03	+3.3 Vdc, 10 A/ 7.5 A
	05	+5 Vdc, 10 A/ 7.5 A
	12	+12 to +12.1 Vdc, 8.0 A/ 6.0 A
	12L	+12 to +12.1 Vdc, 4.0 A/ 3.0 A
	15	+15 Vdc, 6.5 A/ 4.9 A
	15L	+15 Vdc, 3.3 A/ 2.5 A
	24	+24 Vdc, 4.0 A/ 3.0 A
Output # 3	12	±12 Vdc, 4.0 A/ 3.0 A
	12R	±12 Vdc, 2.0 A/ 1.5 A
	15	±15 Vdc, 3.2 A/ 2.4 A
	15R	±15 Vdc, 1.6 A/ 1.2 A
	05	±5.2 Vdc, 10 A/ 7.5 A
	5L	±5.2 Vdc, 5.0 A/ 3.8 A
	5R	±5.2 Vdc, 2.0 A/ 1.5 A
Output # 4	1.8	1.8 Vdc, 3.0 A/ 2.3 A
	02	2 Vdc, 3.0 A/ 2.3 A
	2.5	2.5 Vdc, 3.0 A/ 2.3 A
	03	3.3 Vdc, 3.0 A/ 2.3 A
	05	5.2 Vdc, 5.0 A/ 3.8 A
	5T	5.2 Vdc, 2.5 A/ 1.9 A
	12	12 Vdc, 2.0 A/ 1.5 A
	15	15 Vdc, 1.6 A/ 1.2 A
	16	16 Vdc, 1.6 A/ 1.2 A
	18	18 Vdc, 1.3 A/ 1.0 A
	24	24 Vdc, 2.0 A/ 1.5 A
	24T	24 Vdc, 1.0 A/ 0.8 A
	30	30 Vdc, 1.0 A/ 0.8 A
	32	32 Vdc, 1.0 A/ 0.8 A
48	48 Vdc, 1.0 A/ 0.8 A	
Customer Code (Option)	X	A thru Z
	Y	A thru Z

- Remark :
1. Output # 3 is option for -ve or +ve output voltage.
 2. Output # 4 is floating for output voltage.
 3. The power supply will have a minimum of one output and a maximum of four.
 4. The max. output power for Model SC150U48A and SC150U48B are 170W under forced air cooled.